

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	2111	N/A		
	kW	1688	N/A		
Prime Power (PRP)	kVA	1900	N/A		
	kW	1520	N/A		

TBA

Engine				
Manufacturer		CUMMINS		
Origin		U.K.		
Model		QSK60-G3		
No of Cylinder / Configuration		16 - V TYPE		
Displacement	lt	60,2		
Bore / Stroke	mm	159 / 190		
Compression Ratio		14,5:1		
Aspiration		Turbocharged and Low Temperature Aftercooled (2P/2L)		
Governor Type		ELECTRONIC		
Cooling System		WATER		
Coolant Capacity	lt	191		
Lubrication Oil Capacity	lt	261		
Electrical System	VDC	24		
Speed / Frequency		1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power	kWm	1790	N/A	
Fuel Consumption	lt/h	110 %	406	N/A
		100 %	363	N/A
		75 %	270	N/A
		50 %	190	N/A
Exhaust Outlet Temperature	°C	440	N/A	
Exhaust Gas Flow	lt/s	5525	N/A	
Combustion Air Flow	lt/s	2255	N/A	
Cooling Air Flow	m³/min	TBA	N/A	





Standby Power

Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator			
Manufacturer		MARELLI	
Origin		ITALY	
Model		MJB500SC4	
No of Phase		3	
Power Factor		0,8	
No of Bearing		SINGLE	
No of Poles		4	
No of Leads		6	
Voltage Regulation (Steady State)		± %0,5	
Insulation Class		H	
Degree of Protection		IP 23	
Excitation System		AVR (Automatic Voltage Regulator), Brushless	
Connection Type		STAR	
Total Harmonic Content (No Load)		< %2	
Frequency	Hz	50	60
Voltage Output	VAC	230 / 400	254 / 440
Rated Power (Standby)	kVA	2200	2500
Efficiency	%	96,1	96,3



	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	2468 x 9145 x 3100	23750	2720	TBA
Open Skid	2000 x 5320 x 2610	16250	3000	TBA

- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.



TBA: To Be Ask TBD: To Be Determined NA: Not Available N/A: Not Applicable

TTD2100CM0508-EN